

Table of Contents

Beacon Scripts	3
<i>beaconpublish.sh</i>	3
help	3
<i>beaconsync.sh</i>	3
help	3

Beacon Scripts

Developers should run these scripts with sudo.

```
sudo /root/scripts/beaconpublish.sh
sudo /root/scripts/beaconsync.sh
```

beaconpublish.sh

Used to publish the current state of the website on dev to prod. This includes only html, php, css, etc.. not the database or any dynamically generated content.

help

```
beaconpublish.sh
Usage: beaconpublish.sh [OPTION]...

OPTIONS:
  -d          delete mode, syncs files in delete mode.
               if a file does not exist on dev, but does exist on prod
               the file on prod will be deleted.
               the user will be prompted before any deletions happen
  -h          print this help
```

beaconsync.sh

Syncs stuff from prod to dev to make sure dev is a functional environment for development. Sync includes things like images and database.

help

```
beaconsync.sh
Usage: beaconsync.sh [OPTION]

Sync database, images and other stuff from prod to dev.

OPTIONS:
  -h          print this help
```

From:

<https://wiki.beacontechnology.com/> - **Guide**

Permanent link:

<https://wiki.beacontechnology.com/doku.php?id=wiki:beaconscripts>

Last update: **2021/09/20 19:52**

